

Configuration for Neonatal and Infant Invasive Ventilation

**F&P™ 850 System:
Adaptable Humidification**

- Designed for use with adult, pediatric and neonatal patients to humidify invasive ventilation, Optiflow™ nasal high flow therapy and noninvasive ventilation

Reliable Performance

- One-touch therapy selection combined with dual temperature feedback systems
- Flow-sensor technology for improved safety and humidity delivery
- Built-in algorithms designed to reduce circuit condensate

Evaqua™ 2 Circuits Minimize Condensate

- Minimizes expiratory limb mobile condensate
- Reduces the need for clinician intervention to break open the expiratory limb
- Reduces ventilation issues (auto-PEEP, ventilator dysynchrony) caused by mobile condensate
- No water traps to empty
- Reduces condensate buildup in expiratory filters

Ventilator
(not supplied by F&P)

Waterbag or Bottle
(not supplied by F&P)

Humidification Chamber
MR290

Respiratory Humidifier
MR850XXX

Circuit
RT265
for flows above 4 L/min
RT266
for flows between 0.3-4 L/min
RT267
for SLE2000 ventilators -
4-15 L/min flow range
RT268
for SLE4000/5000 ventilators -
4-15 L/min flow range
RT269
for SLE6000 ventilators -
4-15 L/min flow range

Heater-wire Adapter
900MR805
Temperature & Flow Probe
900MR868
900MR869

Interface
Standard ETT or tracheostomy
(not supplied by F&P)

Some products are unavailable in certain markets