

F&P 850

BREATHING CIRCUITS (Adult)

RT319 - Bi-level/CPAP Circuit



Specifications

Interface Connections	ISO 5356-1 Conical Connectors
Compressible Volume	1.7 L
Compliance @ 60 cmH₂O	5.12 ± 0.32 mL/cmH ₂ O (including 0.03 mL/cmH ₂ O measurement uncertainty)
Resistance to Flow @ 30 L/min With accessories Without accessories	1.1 ± 0.04 cmH ₂ O 0.26 ± 0.04 cmH ₂ O (including 0.03 cmH ₂ O measurement uncertainty)
Circuit Length	1.8 m
Gas Leakage @ 60 cmH₂O	<40 mL/min
Humidifier Compatibility	Compatible with Fisher & Paykel Healthcare MR850 Humidifiers. Refer to humidifier user instructions.
Duration of Use	7 days
Use	Single patient
Shelf Life	5 years

Performance | Specifications

Overall Performance at 20 °C to 26 °C Ambient Temperature	Noninvasive Mode (Mask Mode)	Invasive Mode
Humidification Output	>12 mg/L	>33 mg/L
Flow Rate	3-120 L/min	16-60 L/min

Circuit components and composition | Specifications

Pack Components Dryline 0.5 m, Inspiratory Limb-Large, Pressure Line, Flexitube, Exhalation Port, Non-DEHP MR290V, Chamber, Clip Easy Swivel, Vision Clip, Change Out Label, Inspiratory Filter	
Filter Included? Y/N	Yes
Manufacturing Mode	Produced in a Controlled Working Environment
Disposal	Incineration or according to hospital protocol

Materials | Specifications

Chamber	Adhesive, Aluminium, Ink, Polyethylene, polypropylene, PET, Copper, Polyester, TPE, Acetal, Non DEHP PVC, Polycarbonate, Polystyrene, ABS, Silicone
Other Components (Circuit)	Polyethylene, polypropylene, modacrylic, PET, Copper, TPE, Acetal
Contains DEHP? Y/N	No
Contains Latex? Y/N	No
Mercury Content	Not made with materials containing mercury or mercury compounds

Chamber (MR290) | Specifications

Interface Connections	ISO 5356-1 Conical Connectors
Gas Ports	22 mm Male
Compressible Volume	280 mL
Compliance	0.4 mL/cmH ₂ O
Resistance to Flow @ 60 L/min	0.52 cmH ₂ O
Maximum Operating Pressure	8 kPa
Maximum Peak Flow	180 L/min for 30 sec
Gas Leakage	<10 mL/min

Packaging | Specifications

Carton Dimensions	430 x 205 x 775 mm (16.9 x 8.1 x 30.5 inches)
Carton Weight	5.13 kg (11.3 lbs)
Carton Quantity	Box of 10 Circuit Kits
Packaging Material	Cardboard box

Regulatory | Specifications

Classification	Au IIa, Eu IIa, Canada 2, Japan II
Country of Origin	New Zealand
Intended Use	The RT319 circuit is indicated for use by medical professionals with adult patients requiring respiratory support, Bi-level or CPAP therapy.
Notified Body Identification Number	TÜV SÜD Product Services GmbH CE 0123
GTIN Number	09420012430342 (EA) 09420012414175 (PAC)
UNSPSC Number	42272224
GMDN Code	37706