F&P Optiflow™ Junior 2

Next generation care



Blender Transition Kits

SPECIFICATIONS

| | | (o o o | 00 | 000 | |
|----------------------------------|--|---|---|---|--|
| PRODUCT | OJR410B | OJR412B | OJR414B | OJR416B | OJR418B |
| NASAL CANNULA SIZE | XS | S | М | L | XL |
| Description | F&P Optiflow™ Junior 2 Blender Transition Kit – XS | F&P Optiflow™ Junior 2 Blender Transition Kit – S | F&P Optiflow™ Junior 2 Blender Transition Kit – M | F&P Optiflow™ Junior 2 Blender Transition Kit – L | F&P Optiflow™ Junior 2 Blender Transition Kit – XL |
| Weight (per kit) | 31.2 g | 31.6 g | 33.8 g | 38 g | 38.3 g |
| FLOW RATES* (L/min) - MR850 | | | | | |
| BC151 BC161 BC153 BC163 | 4-8 | 4-9 | 4-10 | 4-15 | 4-15 |
| COMPATIBLE SPARES | | | | | |
| F&P Wigglepad™ 2 | WJR110 | | WJR112 | | |
| PRODUCT SPECIFICATIONS | | | | | |
| Compatible circuits | BC151, BC161, BC153, BC163 | | | | |
| Connection | Easy-click connector, adaptor | | | | |
| Compatible humidifier | MR850 (in invasive mode) | | | | |
| Quantity | Box of 5 | | | | |
| Box components | F&P Optiflow Junior nasal cannula, proprietary adaptor, OJR215 pressure relief manifold, user instructions | | | | |

^{*} Flow rates above describe technical capability of the product when used at sea level. Ensure clinical judgement is used when prescribing flow rates.



Next generation care

Blender Transition Kits | SPECIFICATIONS

| PERFORMANCE SPECIFICATIONS | | | | |
|--------------------------------|---|--|--|--|
| Ambient range | 18-26 °C / 64-79 °F | | | |
| Usage | Single patient use | | | |
| Duration of use | 7 days | | | |
| Recommended gas source | Medical gas | | | |
| Shelf life | 3 years | | | |
| Nominal relief pressure | 40 cmH ₂ O | | | |
| COMPONENTS AND COMPOSIT | ION | | | |
| Cannula predominant materials | Thermoplastic Elastomer; Hydrocolloid; ABS; Stainless steel | | | |
| Adaptor predominant materials | Polypropylene | | | |
| Manifold predominant materials | Thermoplastic Elastomer White; ABS; Stainless steel; Silicon rubber | | | |
| Materials not present | Not manufactured with natural rubber latex, PVC or Phthalates (DEHP, DBP, BBP) | | | |
| Manufacturing mode | Produced in a controlled working environment | | | |
| Disposal | Incineration or according to hospital protocol for cannula, manifold and adapter; Clamshell packaging and label recyclable PET | | | |
| REGULATORY | | | | |
| Classification | AU-IIa, EU-IIa, Canada-II, US-II | | | |
| Country of origin | New Zealand | | | |
| Notified body | TÜV SÜD Product Services GmbH CE0123 | | | |
| Standard | Medical tapers used comply with ISO 5356-1 | | | |

Please note that the information in this specifications sheet (including product information and images) is summarized and provided for illustrative purposes only. Please refer to the relevant user instructions for more information and confirm details with your local Fisher & Paykel Healthcare representative prior to placing an order. Information subject to change without notice.

