














Ventilator Transition Kits

SPECIFICATIONS

	 OJR410VT	 OJR412VT	 OJR414VT	 OJR416VT	 OJR418VT
PRODUCT	OJR410VT	OJR412VT	OJR414VT	OJR416VT	OJR418VT
NASAL CANNULA SIZE	XS	S	M	L	XL
Description	F&P Optiflow™ Junior 2 Ventilator Transition Kit - XS	F&P Optiflow™ Junior 2 Ventilator Transition Kit - S	F&P Optiflow™ Junior 2 Ventilator Transition Kit - M	F&P Optiflow™ Junior 2 Ventilator Transition Kit - L	F&P Optiflow™ Junior 2 Ventilator Transition Kit - XL
Weight (per kit)	8.9 g	9.3 g	11.5 g	15.7 g	16 g
COMPATIBLE SPARES					
F&P Wigglepad™ 2	 WJR110		 WJR112		
PRODUCT SPECIFICATIONS					
Compatible circuits	RT266, RT265				
Connection	Easy-click connector				
Compatible humidifier	MR850 (in invasive mode)				
Quantity	Box of 5				
Box components	F&P Optiflow Junior nasal cannula, proprietary adaptor, user instructions				
PERFORMANCE SPECIFICATIONS					
Ambient range °C	18-26 °C / 64-79 °F				
Usage	Single patient use				
Duration of use	7 days				
Recommended gas source	Medical gas				
Shelf life	3 years				
COMPONENTS AND COMPOSITION					
Predominant materials	Thermoplastic Elastomer; Hydrocolloid; ABS; Stainless steel Adaptor: Polypropylene				
Materials not present	Not manufactured with natural rubber latex, PVC or Phthalates (DEHP, DBP, BBP)				
Manufacturing mode	Produced in a controlled working environment				
Disposal	Incineration or according to hospital protocol for cannula and adaptor; Clamshell packaging and label recyclable PET				
REGULATORY					
Classification	AU-IIa, EU-IIa, Canada-II, US-I				
Country of origin	New Zealand				
Notified body	TÜV SÜD Product Services GmbH CE0123				

Common ventilators

PRODUCT		 OJR410VT	 OJR412VT	 OJR414VT	 OJR416VT	 OJR418VT
NASAL CANNULA SIZE		XS	S	M	L	XL
FLOW RATES* (L/min) 	RT265	4-8	4-9	4-10	4-15	4-15
	RT266	1-4	1-4	1-4	1-4	1-4

Draeger Babylog VN500 Ventilator

Draeger Evita Infinity V500 Ventilator

Flow rates achieved in Neonatal and Pediatric modes.

Pressure limit 30 cmH₂O

Ventilator mode O₂ therapy

Maquet Servo-U Ventilator

Flow rates achieved in Neonatal and Pediatric modes.

Pressure limit 50 cmH₂O

Ventilator mode High flow

Hamilton-S1 Ventilator

Hamilton-G5 Ventilator

Flow rates achieved in Neonatal and Pediatric modes.

Pressure limit 60 cmH₂O

Ventilator mode High flow O₂

* Flow rates above describe technical capability of the product when used at sea level.

Ensure clinical judgement is used when prescribing flow rates.

Maximum flow rates achieved are ventilator dependent.

Product tested under simulated conditions, maximum achievable flow rate may be patient dependent.

Refer to the manufacturer's instructions for correct usage.

Please note that the information in this specifications sheet (including product information and images) is summarized and provided for illustrative purposes only. Please refer to the relevant user instructions for more information and confirm details with your local Fisher & Paykel Healthcare representative prior to placing an order. Information subject to change without notice.