



OJR520 Nasal Cannula | **SPECIFICATIONS**

 OJR520 XXL	 MR850	 AIRVO 2
COMPATIBLE ACCESSORIES		
F&P Wigglepad™ 2	 WJR114	
MAXIMUM FLOW RATES* (L/min)		
	1-36	10-50
PRODUCT SPECIFICATIONS		
Compatible circuit	RT330, OPT014	900PT531, 900PT561
Canula weight	28.2 g	
Connection	Easy-click connector	
Quantity	Box of 10	
Box components	F&P Optiflow Junior 2+ nasal cannula, user instructions	
PERFORMANCE		
Ambient range °C	18 – 26 °C / 64 – 79 °F	
Humidifier mode	Invasive mode	Default mode
Usage	Single patient use; Maximum 7 days	
Duration of use	7 days	
Recommended gas source	Medical gas	
COMPONENTS AND COMPOSITIONS		
Predominant materials	Thermoplastic Elastomer; Hydrocolloid; ABS	
Materials not present	Not manufactured with natural rubber latex, PVC or Phthalates (DEHP, DBP, BBP)	
Manufacturing mode	Non-invasive device; Produced in a controlled working environment	
Disposal	Incineration or according to hospital protocol for cannula; Clamshell packaging and label recyclable PET	
REGULATORY		
Classification	AU-IIa, EU-IIa, Canada-II, US-I	
Country of origin	New Zealand	
Notified body	TÜV SÜD Product Service GmbH CE0123	

* Flow rates above describe technical capability of the product when used at sea level. Ensure clinical judgement is used when prescribing flow rates.

Please note that the information in this specifications catalogue (including product information and images) is summarized and provided for illustrative purposes only. Please refer to the relevant user instructions for more information and confirm details with your local Fisher & Paykel Healthcare representative prior to placing an order. Information subject to change without notice.